

Application No. 10/692848
Amendment dated 24 December 2004
Reply to Office Action of 5 October 2004

Page 3 of 14

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in this application:

Listing of Claims:

1. (Cancelled)
2. (Currently Amended) ~~A switch according to claim 1~~ An optical cross-connect switch for switching optical communications signals, the switch comprising:
 a first pattern projector configured to project one or more first control signal radiation patterns;
 a plurality of output optical channels;
 a plurality of output encoders, each output encoder associated with one of the plurality of output optical channels, each output encoder positioned, relative to the associated output optical channel and the first pattern projector, to receive the one or more first control signal radiation patterns and to detect at least a portion of one or more corresponding output Moiré interference patterns produced by the one or more first control signal radiation patterns;
 wherein each output encoder is configured to generate a corresponding output control signal indicative of an intensity of detected output Moiré interference patterns;
 wherein each output encoder comprises an associated output reticle, each output reticle having a spatially varying pattern of interaction with radiation incident thereon.
3. (Original) A switch according to claim 2 wherein each output reticle is positioned to receive the one or more first control signal radiation patterns and to produce

Application No. 10/692848
Amendment dated 24 December 2004
Reply to Office Action of 5 October 2004

Page 4 of 14

the one or more corresponding output Moiré interference patterns in response thereto.

4. (Original) A switch according to claim 3 wherein each output encoder comprises an associated output radiation sensor, each output radiation sensor positioned to detect at least a portion of the one or more corresponding output Moiré interference patterns and configured to generate the corresponding output control signal.
5. (Original) A switch according to claim 4 comprising:
 - a second pattern projector configured to project one or more second control signal radiation patterns;
 - a plurality of input optical channels;
 - a plurality of input encoders, each input encoder associated with one of the plurality of input optical channels, each input encoder positioned, relative to the associated input optical channel and the second pattern projector, to receive the one or more second control signal radiation patterns and to detect at least a portion of one or more corresponding input Moiré interference patterns produced by the one or more second control signal radiation patterns;wherein each input encoder is configured to generate a corresponding input control signal indicative of an intensity of detected input Moiré interference patterns.
6. (Original) A switch according to claim 5 wherein each input encoder comprises an associated input reticle, each input reticle having a spatially varying pattern of interaction with radiation incident thereon.

Application No. 10/692848
Amendment dated 24 December 2004
Reply to Office Action of 5 October 2004

Page 5 of 14

7. (Original) A switch according to claim 6 wherein each input reticle is positioned to receive the one or more second control signal radiation patterns and to produce the one or more corresponding input Moiré interference patterns in response thereto.
8. (Original) A switch according to claim 7 wherein each input encoder comprises an associated input radiation sensor, each input radiation sensor positioned to detect at least a portion of the one or more corresponding input Moiré interference patterns and configured to generate the corresponding input control signal.
9. (Original) A switch according to claim 8 comprising a controller connected to receive the input and output control signals, the controller configured to determine a position of each output reticle based on the corresponding output control signal and configured to determine a position of each input reticle based on the corresponding input control signal.
10. (Original) A switch according to claim 4 comprising a controller connected to receive the output control signals, the controller configured to determine a position of each output reticle based on the corresponding output control signal.
11. (Original) A switch according to claim 4 wherein each of the output reticles has a spatially varying transmissivity and each associated output radiation sensor is located to detect radiation from the one or more first control signal radiation patterns that has passed through the associated output reticle.

Application No. 10/692848
Amendment dated 24 December 2004
Reply to Office Action of 5 October 2004

Page 6 of 14

12. (Original) A switch according to claim 4 wherein each of the output reticles has a spatially varying reflectivity and each associated output radiation sensor is located to detect radiation from the one or more first control signal radiation patterns that has reflected from the associated output reticle.
13. (Original) A switch according to claim 4 wherein each output reticle is patterned with a regular array of cells.
14. (Original) A switch according to claim 13 wherein each of the cells comprises an aperture portion and an opaque portion and wherein each output reticle passes a first proportion of the first control signal radiation patterns incident on the aperture portion to the associated output radiation sensor and each output reticle passes a second proportion, smaller than the first proportion, of the first control signal radiation patterns incident on the opaque portion to the associated output radiation sensor.
15. (Original) A switch according to claim 4 wherein each output reticle comprises a circularly symmetric pattern of aperture areas and opaque areas and wherein each output reticle passes a first proportion of the first control signal radiation patterns incident on the aperture areas to the associated output radiation sensor and each output reticle passes a second proportion, smaller than the first proportion, of the first control signal radiation patterns incident on the opaque areas to the associated output radiation sensor.

Application No. 10/692848
Amendment dated 24 December 2004
Reply to Office Action of 5 October 2004

Page 7 of 14

16. (Original) A switch according to claim 4 wherein each of the one or more first control signal radiation patterns comprises a plurality of elongated stripes of radiation.
17. (Original) A switch according to claim 4 wherein each of the one or more first control signal radiation patterns comprises a spatially periodic radiation pattern.
18. (Original) A switch according to claim 13 wherein each of the one or more first control signal radiation patterns comprises a spatially periodic radiation pattern having a period substantially equal to a spatial periodicity of the cells on the output reticles.
19. (Original) A switch according to claim 18 wherein the cells on the output reticles are arranged in rows extending substantially parallel to a first axis and columns extending substantially parallel to a second axis and each of the one or more first control signal radiation patterns comprises elongated stripes which are oriented substantially parallel to one of the first and second axes.
20. (Original) A switch according to claim 4 wherein the one or more first control signal radiation patterns comprise at least one radiation pattern having a first wavelength and at least one radiation pattern having a second wavelength.
21. (Original) A switch according to claim 4 wherein the first pattern projector comprises an array of first radiation emitting devices located in positions optically opposing the plurality of output optical channels.

Application No. 10/692848
Amendment dated 24 December 2004
Reply to Office Action of 5 October 2004

Page 8 of 14

22. (Original) A switch according to claim 21 wherein the first pattern projector is configured to project the one or more first control signal radiation patterns by turning on selected pluralities of the first radiation emitting devices.
23. (Original) A switch according to claim 4 wherein each output encoder comprises an associated output lens, each output lens located to focus the one or more first control signal radiation patterns onto the associated output reticle.
24. (Original) A switch according to claim 23 wherein each output lens is also located to couple an optical communication signal from a selected one of a plurality of input optical channels into the associated output optical channel.
25. (Original) A switch according to claim 4 wherein each output reticle is coupled to move with the associated output optical channel, and wherein the one or more corresponding output Moiré interference patterns vary in intensity based on a position of the associated output reticle.
26. (Original) A switch according to claim 25 wherein the output optical channels comprise optical fibers.
27. (Original) A switch according to claim 4 wherein each output reticle is coupled to move with an associated moveable optical element, and wherein the one or more corresponding output Moiré interference patterns vary in intensity based on a position of the associated output reticle.

Application No. 10/692848
Amendment dated 24 December 2004
Reply to Office Action of 5 October 2004

Page 9 of 14

28. (Original) A switch according to claim 27 wherein a position of each moveable optical element influences an optical path of an optical communication signal coupled into the associated output optical channel.
29. (Original) A switch according to claim 28 comprising a controller connected to receive the output control signals from the output radiation sensors, the controller configured to determine a position of each moveable optical element based on the corresponding output control signal.
30. (Original) A switch according to claim 4 comprising a plurality of output actuators, each output actuator associated with one of the plurality of output optical channels and each output actuator comprising: a magnetic member coupled to move with the associated output optical channel and a plurality of magnetically polarizable branches spaced apart around the magnetic member.
31. (Original) A switch according to claim 30 wherein each magnetic member is circularly symmetric.
32. (Original) A switch according to claim 30 wherein each magnetic member comprises a ring of magnetic material.
33. (Original) A switch according to claim 32 wherein each ring extends around a peripheral edge of the associated output reticle.
34. (Original) A switch according to claim 30 wherein each output actuator comprises four branches equally spaced apart around the magnetic member.

Application No. 10/692848
Amendment dated 24 December 2004
Reply to Office Action of 5 October 2004

Page 10 of 14

35. (Currently Amended) An optical cross-connect switch according to claim 2 wherein each output optical channel comprises an optical fiber, ~~switch comprising a system for independently determining positions of each of a plurality of optical fibers in the optical switch, the system comprising:~~
 ~~a plurality of reticles each wherein each reticle is~~ coupled to move with a corresponding one of the optical fibers, ~~each of the reticles having a spatially varying pattern of interaction with radiation incident on the reticle;~~
 ~~a wherein the first pattern projector is~~ configured to project first and second control signal radiation patterns onto all of the plurality of ~~reticles;~~ and reticles, and
 ~~a plurality of radiation sensors, each of which is~~ wherein each output encoder comprises a radiation sensor associated with ~~a~~ its reticle, each radiation sensor located to generate a control signal indicative of an intensity of radiation of the first and second control signal radiation patterns which has interacted with ~~the~~ its associated reticle.
36. (Original) An optical switch according to claim 35 comprising a data processor connected to receive the control signal from each of the radiation sensors and configured to compute a position of the associated reticle from the control signal.
37. (Original) An optical switch according to claim 35 wherein each reticle has spatially varying transmissivity and the associated radiation sensor is located to detect radiation from the pattern projector which has passed through the reticle.

Application No. 10/692848
Amendment dated 24 December 2004
Reply to Office Action of 5 October 2004

Page 11 of 14

38. (Original) An optical switch according to claim 35 wherein each reticle has spatially varying reflectivity and the associated radiation sensor is located to detect radiation from the pattern projector which has been reflected from the reticle.
39. (Original) An optical switch according to claim 36 wherein each reticle is patterned with a regular array of cells.
40. (Original) An optical switch according to claim 39 wherein each of the cells comprises an aperture portion and an opaque portion and wherein each reticle passes a first proportion of radiation incident on the aperture portion from the pattern projector to the associated radiation sensor and each reticle passes a second proportion, smaller than the first proportion, of the radiation incident on the opaque portion from the pattern projector to the associated radiation sensor.
41. (Original) An optical switch according to claim 39 wherein the first and second radiation patterns comprise spatially periodic patterns having periods equal to a spatial periodicity of the cells.
42. (Original) An optical switch according to claim 41 wherein the cells are arranged in rows extending substantially parallel to a first axis and columns extending substantially parallel to a second axis and the first and second radiation patterns respectively comprise elongated stripes oriented substantially parallel to the first and second axes.

Application No. 10/692848
Amendment dated 24 December 2004
Reply to Office Action of 5 October 2004

Page 12 of 14

43. (Original) An optical switch according to claim 35 comprising a lens associated with each of the optical fibers, wherein each lens is located to focus the first and second radiation patterns onto the associated reticle.
44. (Original) An optical switch according to claim 43 wherein each lens is located to focus optical communication signals into an end of the associated optical fiber.
45. (Original) An optical switch according to claim 35 comprising an actuator associated with each of the plurality of optical fibers, each actuator comprising a magnetic member coupled to move with the associated optical fiber and a plurality of magnetically polarizable branches spaced apart around the magnetic member.
46. (Original) An optical switch according to claim 36 wherein the interaction between each reticle and the first radiation pattern creates an associated first Moiré interference pattern and wherein the radiation sensor associated with the reticle is located to detect an intensity of the associated first Moiré interference pattern and to generate the control signal in response thereto.

Application No. 10/692848
Amendment dated 24 December 2004
Reply to Office Action of 5 October 2004

Page 13 of 14

47. (Original) An optical switch according to claim 46 wherein the interaction between each reticle and the second radiation pattern creates an associated second interference pattern and wherein the radiation sensor associated with the reticle is located to detect an intensity of the associated second Moiré interference pattern and to generate the control signal in response thereto.

48.-67. (Cancelled)